

THERPOL OG70

THERPOL OG70 is a worldwide innovation, it is a thermoplastic rubber with excellent fluidity properties, proportioning a significant improvement in flexibility and impact resistance to Polypropylene, Polyethylene, Polystyrene and ABS. As a rubber, it also adds significant impact resistance to plastic compounds when mixed with **THERPOL OG70** for low temperature applications.

Polypropylene and Polyethylene compounds were obtained with excellent flexibility and rebound even in very high hardness using **THERPOL OG70** as additive.

Main characteristics

- ✓ Granulated Rubber Compound
- ✓ Increase in Impact Resistance
- ✓ High Elongation
- ✓ High Rebound
- ✓ Injection Temperature Reduction
- ✓ Excellent Rubber Texture to Plastic
- ✓ 100% Recyclable

Recommended applications

- ✓ Pallets, Chairs and Tables Manufacturing
- ✓ Pipes and Connections
- ✓ Boxes for Fish, Fruits and Beverages
- ✓ Floor Plates
- ✓ Properties Improvement for Recycled PP, PE, PS, PET and ABS
- ✓ General Plastic Products

Physical Properties

Physical	Nominal	Method
Density	0,950+/-0,05 g/cm ³	ASTM D792
Mooney Viscosity (ML 1+4 a 120°C)	5,0 +/- 3 MU	ASTM D1646
Mechanical	Nominal	Method
Tensile Strenght	6,08 MPa	ASTM D412
Elongation	425%	ASTM D412
Tear Strenght	20,63 kN/m	ASTM D624
Hardness	Nominal	Method
Shore A	72pts	ASTM D2240
Thermal	Nominal	Method
Low temperature resistance	-40°C	Proquitec

Packing

15 Kg bags

Shelf Life

12 Months

As informações e recomendações aqui contidas constituem um serviço aos nossos clientes. A Proquitec SA declara que tais informações e recomendações foram obtidas de fontes idôneas não assumindo, dessa forma, qualquer responsabilidade pelo uso inadequado de seus produtos.